



3.5" Internal Card Reader + USB2.0 1 port

Model No.: INCR637M

Features:

- Easily mount into 3.5" drive bay.
- Supports DOS bootable function replacing your floppy disk drive.
- Includes both beige and black color bezel for swapping.
- Support high-speed data transfer rate up to 480Mbps.
- Support Bus-powered, No external power required.
- Supports hot swapping and Plug-and-Play capability.
- Memory Cards supported CompactFlash I/II, IBM Micro drive, SmartMedia, Secure Digital(SD), Mini SD, Multimedia Card (MMC), Memory stick (MS), Memory stick Pro , MS-Duo, MS-Pro Duo, Magic Gate Memory Stick, RS Multi Media Card, High Speed Memory Stick, Flash Memory Stick and other cards.
- Four media slots can be used at the same time for data exchange.

Specification:

Data Transfer Rate:	Supports high-speed 480 Mbps / full-speed 12 Mbps / low-speed 1.5 Mbps
Media Supports:	CF: CompactFlash Type I/II, Microdrive SD: SD, Mini SD (supported SDHC) SM: SmartMedia MMC: MMC, RS-MMC MS: MS, MS-Pro(4-Bit), MS-Duo, MS-PDuo



Forcom Technology Co., Ltd.

Tel: +886-2-77296880 Fax: +8862-27055495

e-mail: info@forcomtech.com.tw

URL: <http://www.forcomtech.com.tw>

Interface & Pin Assignment:	USB pin housing for motherboard installation P1-Red-Vbus+ P2-white-D- P3-Green-D+ P4-Black-GND P5-Black-Shielding
Indicators:	One read/write active LED
Environmental:	Operating Temperature: 5°C ~ 40°C Storage Temperature: -20°C ~ 60°C Operating Humidity: 0%~80% RH, non-condensing
Dimensions:	100*120*25.4 mm (L*D*H)
Certification:	FCC Class B, CE

System Support

- Windows98/SE, Windows2000, WindowsME, WindowsXP®, VISTA, WIN7
- Mac OS 8.6 or higher
- Linux OS 2.4.X or higher