



PCI Express 4 Lane USB3.0 + SATA III 2+2 port card

MODEL NO.: PEU3S3

Features

- PCI Express Base Specification Rev. 2.0
- PCI Express Card Electromechanical Rev. 2.0
- Serial ATA AHCI Spec. Rev.1.3
- Serial ATA Revision 3.0
- One lane PCI Express for 2.5 and 5GHz signaling
- Single virtual channel
- ECRC and Advanced Error Reporting capability
- 2 ports Serial ATA PHY for 1.5, 3.0 and 6.0GHz signaling
- Support IDE/AHCI mode
- Support Native Command Queue (NCQ)
- Support Gen1m and Gen2m SATA PHY
- Support Port Mult Compliant with Universal Serial Bus 3.0 specification Revision 1.0.
- Compliant with xHCI (eXtensible Host Controller Interface) specifications Revision 1.0.
- Supports simultaneous operation of multiple USB 3.0, USB 2.0 and USB 1.1 devices.
- Expands two external USB3.0 Super-Speed ports on the system.
- Hot-swapping feature allows you to connect/disconnect devices without powering down the system.
- Certified by CE, FCC, RoHS, and Microsoft WQHL approval.



Forcom Technology Co., Ltd.

Tel: +886-2-77296880 Fax: +886-2-27055495

e-mail: info@forcomtech.com.tw

URL: <http://www.forcomtech.com.tw>

Specification Specification

Bus Type	PCI Express
Chipset ID	ASMEDIA ASM1061& Etron EJ168
Number of Ports	2 external USB3.0 & 2 Port Internal <i>SATA III</i>
Transfer Rate	SATA III transfer rate of 6.0Gbps, 3.0Gbps, 1.5Gbps Data Transfer rate of 1.5/12/480/5000 Mbps.
Dimensions	69 (W) x 130 (L) mm
Environment	Operating Temperature: -0°C to 50°C (32°F to 122°F) Storage Temperature: -20°C to 60°C (-4°F to 140°F)
OS Compatibility	Windows 2000/XP/Vista/7(32/64-bit) Windows Server 2003/2008 Linux 2.6.32
Bracket	Standard 121mm/Low profile 79.2mm

Accessories:

- 1 x PCI Express USB 3.0 & *SATA III* card
- 1 x Driver CD
- 1 x Instruction Manual