



3.5" Internal Card Reader + USB2.0 1 port

Model No.: INCR-U2

Features:

Easily mount into 3.5" drive bay.

Supports DOS bootable function replacing your floppy disk drive.

Includes both beige and black color bezel for swapping.

Support high-speed data transfer rate up to 480Mbps.

Support Bus-powered, No external power required.

Supports hot swapping and Plug-and-Play capability.

Memory Cards supported CompactFlash I/II, IBM Micro drive, SmartMedia, Secure Digital(SD), Mini SD, Multimedia Card (MMC), Memory stick (MS), Memory stick Pro , MS-Duo, MS-Pro Duo, Magic Gate Memory Stick, RS Multi Media Card, High Speed Memory Stick, Flash Memory Stick and other cards.

Four media slots can be used at the same time for data exchange.

Specification:

Data Transfer Rate:	Supports high-speed 480 Mbps / full-speed 12 Mbps / low-speed 1.5 Mbps
Media Supports:	CF: CompactFlash Type I/II, Microdrive SD: SD, Mini SD (supported SDHC) SM: SmartMedia MMC: MMC, RS-MMC MS: MS, MS-Pro(4-Bit), MS-Duo, MS-PDuo



Forcom Technology Co., Ltd.

Tel: +886-2-77296880 Fax: +8862-27055495

e-mail: info@forcomtech.com.tw

URL: <http://www.forcomtech.com.tw>

Interface & Pin Assignment:	USB pin housing for motherboard installation P1-Red-Vbus+ P2-white-D- P3-Green-D+ P4-Black-GND P5-Black-Shielding
Indicators:	One read/write active LED
Environmental:	Operating Temperature: 5°C ~ 40°C Storage Temperature: -20°C ~ 60°C Operating Humidity: 0%~80% RH, non-condensing
Dimensions:	100*120*25.4 mm (L*D*H)
Certification:	FCC Class B, CE

System Support

Windows98/SE, Windows2000, WindowsME, WindowsXP®, VISTA

Mac OS 8.6 or higher

Linux OS 2.4.X or higher