



Model No.: **PEFB210**

FEATURES

General

- Supports PCI Express Base Specification Revision 1.1.
- Single-lane (or x1) PCI Express throughput supports rates of 2.5 Gbps.
- Hot-swapping feature allows you to dis/connect devices without powering down the system.
- Built-in 4-pin power connector for receiving extra power supply from system.

IEEE 1394b

- Compliant with 1394 Open Host Controller Interface Specification 1.1.
- Provides IEEE 1394b software enable better performance of the hardware and data transfer.
- Provides three external and one internal independent FireWire ports.
- Data transfer speeds of 100, 200, 400, and 800 Mbps
- Low-cost peripherals can be powered directly from the 1394 cable, so no dedicated power supply is needed.
- Fully compliant with IEEE P1394b and backwards supports 1394a-2000 as well as 1394-1995 standards.
- Devices can be daisy-chained and no central bus supervision is required.

HARDWARE

- **Type : 1394a+1394b PCI Express Card**
- **PCB dimension=L x W=90mm x 60mm**
- **Chipset : LSI FW643**
- **Interface : PCI Express**
- **Port : 2-port 1394b + 1-Port 1394a**
- **Speed : Max 800Mbps**

OS Support : Windows 98SE/ME/2000/XP/2003/VISTA , Linux2.6 and MAC X